



BH-2 FIXTURED BASKET BLASTERS

FEATURES

- Door available as manual swing or automatic lift up for overhead loading
- TurboShot™ blast wheel design
- Door safety switch
- One button push operation with adjustable cycle times
- Easily replaceable cabinet/liners
- Easy basket jiggling set-up for any shape parts - spring loaded rods
- Automatic reversing cycle for thorough cleaning
- Full load of steel shot abrasive media included; customer choice of S70 - S330
- Shot load ampimeter to maintain proper shot load

OPTIONS

- Motor upgrades for faster performance
- Heavier duty construction
- Removable basket
- Additional baskets
- Special designed fixturing
- Automated kick out basket with table
- Dust collection, sized to fit
- Removable stand control panel
- Factory assist install & training
- Optional voltage:
 - 230V/3PH/50HZ
 - 380V/3PH/50HZ
 - 440V/3PH/60HZ
 - 575V/3PH/60HZ



The BH-2 removes rust, dust, dirt, and other contaminants, without part on part tumbling.

Originally designed to accommodate engine blocks and heads.

Model	Details
Work Envelope	3.69 ft ³
Basket Dimensions	32" l x 23" diameter
Overall Dimensions	66" l x 36.5" w x 75" h
HP of Blast Wheels (STD)	1 - 10HP
Basket HP (STD)	0.5HP
Basket Weight Capacity (Approx.)	500 lbs.
Dust Collector (STD)	DC-1



Before



After