



PS1370 POWER STROKE HONES

FEATURES

- Handles small engines and inline blocks up to 22" long. Can also accommodate Singles, Twins, Triples, and Fours.
- Heavy construction added with the hands-free foot controller eliminate the need for vicing the cylinder down while honing.
- An 7-gallon oil capacity is used to flood the cylinder while honing which results in better cooling and surface finish. All while keeping your shop floor oil-free.
- Fully adjustable stroke speed and use of the rigid AN hone head achieves superior accuracy and bore geometry
- Easy to set-up and be productive thanks to a wide range of honing abrasives
- Exterior cradle clamp handles make it easy to roll cylinders from bank to bank

STANDARD EQUIPMENT

- Oil Pump
- Honing Oil (5-Gallons)
- Work Light
- Power Foot Switch
- 2 - Clamp Rod
- 2 - Quick Knob
- Cylinder Clamp Weldaments
- Chuck & Key
- U-Joint
- Parallel Block
- Upper & Lower Clamps
- Service Manual
- 2 - Clamp Plate Lower
- 2 - Clamp Plate Upper
- Jacobs Chuck & Adapter



The PS1370 Power Stroke Hone is the ideal machine for the motorcycle / small engine shop.

Model	Details
Max. Block Length	22"
Max. Stroke	10"
Honing Range	1.75" - 5.5"
Hone Motor	0.5HP
Coolant Capacity	7 gal.
Air Requirement	100 PSI, 3 CFM
Approx. Machine Weight	500 lbs.
Approx. Shipping Weight	635 lbs.

Hone head #, friction feed, or non-friction feed is optional

Ensures that the cylinder walls are perfectly round, smooth, and have the correct crosshatch pattern, which is essential for optimal engine performance and longevity.

