

PS2300 POWER STROKE HONES

FEATURES

- Handles automotive V6, V8, and inline blocks up to 34" long.
- Air/Oil stroke mechanism ensures smooth operation and consistent crosshatch.
- Ampmeter allows operator to maintain straight round cylinders without stopping to gauge.
- Stroke speed control knob adjusts stroke speed for any crosshatch angle.
- Convenient dwell button on front control panel allows operator to dwell hone head anywhere in cylinder.
- Exterior craddle clamp handles make it easy to roll automotive V8 blocks from bank to bank.

STANDARD EQUIPMENT

- Parallel Riser Assembly
- Quick Knob (0.625")
- Clamp Rods
- Adjustable Clamp Bar (V-Block)
- Dial Bore Gauge Bracket
- AN Style Hone Head and Drive Shaft
- Counterweight
- 5-Gallon Honing Oil
- Accessory Tray
- Inline Block Clamp
- Power Foot Switch
- Work Light
- Hone Oil Pump
- U-Joint
- 150/220/280-Grit
 (2.7" 4.1" short stones)
- Friction Feed Unit

Model	Details
Max. Block Length	34"
Max. Stroke	12"
Honing Range	1.75" - 5.5"
Hone Motor	0.5HP
Coolant Capacity	8 gal.
Air Requirement	100 PSI, 3 CFM
Approx. Machine Weight	900 lbs.
Approx. Shipping Weight	1,079 lbs.

^{*115}V/3PH/60HZ or 220V/1PH/60HZ electrical options*



The PS2300 Power Stroke Hone is a true power stroke machine with power assist.

Hones most small engines and motorcycle cylinders in just a few minutes, and V-8 automotive blocks.



