

PS3301 POWER STROKE HONES

FEATURES

- Handles automotive V6, V8, and inline blocks up to 42" long.
- 1HP gear reduction drive motor and friction feed hone head allows the operator to remove stock fast.
- Ampmeter allows the operator to maintain straight round cylinders without stopping to gauge.
- Stroke speed control knob and air/oil stroke system give operator a smooth consistent crosshatch angle that is infinitely variable.
- Positive bottom stop is adjustable and prevents hone head from hitting main webs.
- Up front carriage traverse handle allows operator to quickly and easily position hone head over cylinder.
- Convenient rollover handle for easy precise leveling of block at any cylinder angle.
- Honing oil filter system ensures clean oil and consistent surface finish.
- Convenient dwell button on front control panel allows operator to dwell hone head anywhere in cylinder.

STANDARD EQUIPMENT

- Parallel Riser Assembly
- Quick Clamp Knobs (0.625")
- Clamp Rods
- Adjustable Clamp Bar (V blocks)
- Dial Gauge Bracket
- Friction Feed Hone Head (AN style)
- Drive Shaft Assembly
- Counterweight
- 10 Gallons Honing Oil
- Honing Stone Tray
- Universal joint
- Tool Tray
- Oil Filter
- Inline Block Clamp
- Power Foot Switch
- Work Light
- Oil Pump
- 3 Set of Hone stones



The PS3301 Power Stroke Hone is a true power stroke hone for auto and truck engine blocks.

The array of features ensures easy and precise leveling, clean oil and consistent finishing with easy loading and unloading.

115V/3PH/60HZ or 220V/1PH/50HZ electrical options





| Model | Details |
|-------------------|----------------|
| Max. Block Length | 42" |
| Max. Stroke | 12" |
| Honing Range | 1.7" - 5.5" |
| Hone Motor | 1HP |
| Coolant Capacity | 13 gal. |
| Air Requirement | 100 PSI, 3 CFM |
| Machine Weight | 1,300 lbs. |
| Shipping Weight | 1,495 lbs. |