



8-FTW FLOW THROUGH WASHER

FEATURES

- 7-day advance heat up timer for early start-up
- Filter debris screen
- Easy controls (On/Off)
- Digital amp meters
- Heavy-duty galvanized belt material
- Insulated wash tank
- Fixed speed conveyor belt
- Conveyor sprockets on entrance
- Conveyor drive sprockets at the exit for belt support and drive

OPTIONS

- 1.5HP power exhaust
- Liquid level control system
- Oil skimmer
- Digital thermostat
- Stainless-steel
- Pump sound insulation package
- Hot air blow-off
- Motor powered steam exhaust
- HMI / PLC touchscreen
- Automatic sludge drag-out conveyor
- Small parts basket



Exhaust



Controls

The 8-FTW was designed to remove oil, grime, grease, dirt, and other contaminants off any part that can fit through the entrance.



| Model | Details |
|-------------------------------------|---------------|
| Wash Tank Capacity | 180 gal. |
| Electrical | 460V/3PH/60HZ |
| Tunnel Opening | 18" x 16" |
| Machine Length | 8' |
| Wash Section with Vestibules | 4' |
| Electric Heat | 30KW |
| Seal-less Pump | 180 GPM |
| Conveyor Belt | 24" w |
| Conveyor Belt Drive | 0.5HP |